



Hotpoint® PTAC with Electric Heat 230/208V, 15amp Model# AH12E07D2B

FEATURES			
Control Type	Electronic		
Fan Speed Selections	3 Cooling 3 Fan Only 3 Heating		
Discharge Grille	2-position		
Product Type	Packaged Terminal Air Conditioners (PTAC)		
Refrigerant Type	R32		
Manual Vent Control	Hidden		
"SmartFan" Fan Cycle	Yes		
Chassis Type	Slide-In		
Fan Motor	2		
Unit Features	Auto Power Recovery Automatic Indoor Frost Control Central Desk Control Compatibility Freeze Sentinel Power Cord (LCDI) included Remote Thermostat Compatibility		
Temperature Range	62 - 80 F		
Heat - Cool	Yes		
Auto Power Recovery	Yes		
Rotary Compressor	Yes		
Outdoor Vent / Exhaust	Yes		
Venting Features	Concealed Manual Vent Control Vent Air Filter		
Heating System	Electric Resistance		

```
Have more questions? Please contact 1-800-626-2000
```





Hotpoint® PTAC with Electric Heat 230/208V, 15amp Model# AH12E07D2B

APPROXIMATE DIMENSIONS(HxDxW)

• 16 H x 42.40 W x 20.90 D

CAPACITY

- Cooling BTUH (MAX) 7200.00000Btu
- CFM Indoor Fan Low 236
- CFM Indoor Fan Medium 339
- CFM Indoor Fan High 334
- Cooling EER (BTUH / Watt) 11.9
- Cooling BTUH (MIN) 7000Btu

APPEARANCE

- Installation Through-the-Wall
- Color Appearance White

WEIGHTS & DIMENSIONS

- Overall Width (in) 42 2/5in
- Approximate Shipping Weight (lb) 112 2/5lb
- Overall Height (in) 16in
- Overall Depth (in) 20 9/10in
- Net Weight (lb) 101 3/5lb

POWER / RATINGS

- Cooling Amperes 2.45/2.6
- Cooling Watts 605/585
- Voltage (MIN) 208V
- Heating Electric Heater Watts 2535/2080
- Voltage (MAX) 230.00000V
- Heating Electric Heater Amps 10.8/9.8

WARRANTY

- · Warranty Notes See written warranty for full details
- Labor Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system

CERTIFICATIONS

 Claims & Certifications - AHRI CSA CUL UL NRCAN