

Hotpoint® PTAC with Electric Heat 230/208V, 15amp *Model# AH12E09D2B*



| FEATURES | |
|------------------------|--|
| Control Type | Electronic |
| Fan Speed Selections | 3 Cooling 3 Fan Only 3 Heating |
| Discharge Grille | 2-position |
| Product Type | Packaged Terminal Air Conditioners (PTAC) |
| Refrigerant Type | R32 |
| Manual Vent Control | Hidden |
| "SmartFan" Fan Cycle | Yes |
| Chassis Type | Slide-In |
| Fan Motor | 2 |
| Unit Features | Auto Power Recovery Automatic Indoor Frost Control Central Desk Control Compatibility Freeze Sentinel Power Cord (LCDI) included Remote Thermostat Compatibility |
| Temperature Range | 62 - 80 F |
| Heat - Cool | Yes |
| Auto Power Recovery | Yes |
| Rotary Compressor | Yes |
| Outdoor Vent / Exhaust | Yes |
| Venting Features | Concealed Manual Vent Control Vent Air Filter |
| Heating System | Electric Resistance |

Have more questions? Please contact 1-800-626-2000



Hotpoint® PTAC with Electric Heat 230/208V, 15amp Model# AH12E09D2B

APPROXIMATE DIMENSIONS(HxDxW)

16 H x 42.40 W x 20.90 D

CAPACITY

- Cooling BTUH (MAX) 9200.000000Btu
- CFM Indoor Fan Low 340
- CFM Indoor Fan Medium 391
- CFM Indoor Fan High 434
- Cooling EER (BTUH / Watt) 11.3
- Cooling BTUH (MIN) 9000Btu

APPEARANCE

- Installation Through-the-Wall
- Color Appearance White

WEIGHTS & DIMENSIONS

- Overall Width (in) 42 2/5in
- Approximate Shipping Weight (lb) 108 7/10lb
- Overall Height (in) 16in
- Overall Depth (in) 20 9/10in
- Net Weight (lb) 98 1/10lb

POWER / RATINGS

- Cooling Amperes 3.5/3.8
- Cooling Watts 810/795
- Voltage (MIN) 208V
- Heating Electric Heater Watts 2535/2080
- Voltage (MAX) 230.000000V
- Heating Electric Heater Amps 10.8/9.8

WARRANTY

- · Warranty Notes See written warranty for full details
- Labor Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system

CERTIFICATIONS

 Claims & Certifications - AHRI CSA CUL UL NRCAN

Have more questions? Please contact 1-800-626-2000