

Hotpoint® PTAC with Electric Heat 7,000 BTU, 230/208V, 15amp Model# AHES07D2XXA



- 2 Fan Speeds
- 4 Temperature-Limiting Options
- Auto Dimming Display
- Slinger Ring Condensate Removal
- Coverless Control Panel
- Automatic Emergency Heat
- Freeze/Frost & Overheat Protection
- Auto Power Recovery
- Self-Diagnostics
- Constant Fan Button

FEATURES	
Control Type	Electronic
Fan Speed Selections	2 Cooling 2 Fan Only 2 Heating
Discharge Grille	2-position
Product Type	Packaged Terminal Air Conditioners (PTAC)
Refrigerant Type	R32
Manual Vent Control	Hidden
"SmartFan" Fan Cycle	Yes
Chassis Type	Slide-In
Fan Motor	1
Unit Features	Auto Power Recovery Automatic Indoor Frost Control Freeze Sentinel Power Cord (LCDI) included Remote Thermostat Compatibility (Accessory Kit Required)
Temperature Range	62 - 80 F
Heat - Cool	Yes
Auto Power Recovery	Yes
Rotary Compressor	Yes
Outdoor Vent / Exhaust	Yes
Venting Features	Concealed Manual Vent Control
Heating System	Electric Resistance

Have more questions? Please contact 1-800-626-2000



Hotpoint® PTAC with Electric Heat 7,000 BTU, 230/208V, 15amp Model# AHES07D2XXA

APPROXIMATE DIMENSIONS(HxDxW)

16 H x 42.40 W x 20.90 D

CAPACITY

- Cooling BTUH (MAX) 7200.00Btu
- Cooling EER (BTUH / Watt) 12.0/12.1
- Cooling BTUH (MIN) 7000Btu

APPEARANCE

- Installation Through-the-Wall
- Color Appearance White

WEIGHTS & DIMENSIONS

- Overall Width (in) 42 2/5in
- Approximate Shipping Weight (lb) 90lb
- Overall Height (in) 16in
- Overall Depth (in) 20 9/10in
- Net Weight (lb) 79lb

POWER / RATINGS

- Cooling Amperes 2.6/2.8
- Cooling Watts 600/575
- Voltage (MIN) 208V
- Heating Electric Heater Watts 2500
- Voltage (MAX) 230.000000V

WARRANTY

- · Warranty Notes See written warranty for full details
- Labor Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system

CERTIFICATIONS

 Claims & Certifications - AHRI CSA CUL UL NRCAN

Have more questions? Please contact 1-800-626-2000